

Concrete Mixers | CT, LS & RG



FEATURES

- Three model sizes,150-100 litre, 200-150 litre and 280-200 litre.
- Totally enclosed "safety lube drive".
- Unbreakable steel mixing drum.
- Full lift engine canopy.

- Heavy duty gear mechanism.
- Drive to drum by stretchless "V" belt.
- Solid rubber wheels for longer life.
- Machine cut crownwheel and bevel pinion made of special toughened heat treated steel.

CONCRETE



Concrete Mixers | CT, LS & RG

CONCRETE MIXERS			
	СТ	LS	RG
Engine	Hatz 1B20	Hatz 1B20	Lister LV1-09
Power	1.5 kW @ 1500 rpm	1.5 kW @ 1500 rpm	1.5 kW @ 1500 rpm
Capacity - Unmixed (litres)	150	200	280
Capacity - Mixed (litres)	100	150	200
Loading Height (mm)	1041	1085	1110
Drum Speed (rpm)	20	21	20
Drum Opening (mm)	483	533	546
Discharge Height (mm)	660	638	580
Length less draw bar (mm)	1727	1910	2040
Width (mm)	813	975	1035
Height - Drum Vertical (mm)	1651	1710	1835
Height - Drum Inverted (mm)	1524	1609	1640
Frame Construction	Welded Steel Channel		
Tyres	Rubber Cushion		
Length (m)	1.78	1.91	2.08
Width (m)	0.83	0.98	1.18
Height (m)	1.56	1.61	1.65
Volume (m³)	2.3	3.01	4.05
Maximum Weight (kg)	404	437	631

TEREX Compact Central Boulevard, Prologis Park, Coventry, England, CV6 4BX

Tel: +44(0)24 7633 9400 Fax: +44(0)24 7633 9500

Email: enquiries@terexce.com www.terexce.com

Dealer

www.terex.com

For further information, please contact your local distributor or the TEREX sales office listed. TEREX pursues a policy of continuous development for its products. Product specifications are subject to change without notice or obligation. The photographs and drawings in this brochure are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. Prices and specifications subject to change without notice. The only warranty applicable is the standard written warranty applicable to the particular product and sale. TEREX makes no other warranties, whether expressed or implied. Copyright ©04.2006